

DIGITAL PC 3010 README.TXT

May 20, 1998

This README.TXT covers information that was unavailable when the DIGITAL PC 3010 documentation was written. It also includes limitations and suggestions.

Intel and AMD 233MHz Processors

If your PC is equipped with a 233MHz processor, the correct voltage and clock speed settings will be set when you receive your system.

If you ever need to adjust or reset these settings, please refer to Appendix A, Technical Specifications, in your DIGITAL PC 3010 System Reference guide. The Main Logic Board Jumper settings table details the necessary jumper settings.

Clock Frequency - both the Intel Pentium II 233 and the AMD-K6 233 processor should be set to the 66 MHz, 3.5 CPU bus speed ratio settings as shown on page A-8.

CPU Voltage - The Intel Pentium II 233 should be set to 2.8 volts and the AMD-K6 233 should be set to 3.2 volts as shown on page A-9.

The DIGITAL Startup Diskette

The DIGITAL Startup diskette is no longer shipped with DIGITAL PCs. Instead, in the event that you are unable to access your computer's operating system, you can use the DIGITAL System Software CD. This CD is a bootable CD and capable of being used to boot a PC on which the hard disk drive has failed. It contains all of the applications, drivers and files necessary to restore DIGITAL-supplied system software.

NOTE: If your computer boots from a diskette or hard disk drive instead of the CD-ROM drive, run the BIOS Setup utility to change the boot sequence. In the Boot menu, make the CD-ROM drive the first entry in the boot priority list, save your changes, then restart the computer. For more information about using the BIOS setup utility, see the System Reference manual included with your DIGITAL PC.

3Com Network Interface Card

Some DIGITAL PC 3010 computers contain the 3Com 3C905B-TX network interface card. The 3Com User Guide is provided on the DIGITAL System Software CD in PDF format. You must have Adobe Acrobat Reader 3.0 installed before you can view or print the file. Adobe Acrobat Reader can also be installed from the DIGITAL System Software CD.

The DIGITAL System Software CD includes an easy-to-use program that allows you to install Adobe Acrobat Reader and view the 3Com User Guide or copy it onto your computer's hard disk drive.

To launch the installation program:

1. Insert the DIGITAL System Software CD into your computer's CD-ROM drive. It should autorun and launch your Internet browser to display your choices.
2. Select whether your PC is running Windows 95 or Windows NT Workstation.
3. A screen listing the installable applications and utilities will display. Select the item you want to install and follow the instructions on the screen. Adobe Acrobat is listed on this screen. The 3Com User Guide is located under "Documentation."

If the DIGITAL System Software CD does not run automatically:

1. Click Start, then click Run.
2. Type D:\SETUP.HTM in the Open box (where D:\ is your CD-ROM drive).
3. Click OK.
4. The installation program will launch and you can select what items on the CD you want to install.

DMA for Devices

Windows 95 on DIGITAL PC 3010

To enable DMA for hard disk drives:

1. From the Control panel, select System.
2. Select Device Manager.
3. Select Disk Drives.
4. Select the individual device.
5. Select the Settings Page.
6. Check/Uncheck DMA to enable/disable DMA for this device.

ClientWORKS

ClientWORKS is Digital Equipment Corporation's latest DMI solution.

ClientWORKS contains the following new DMI features:

- A new 32-bit MifMaker (MIFMKR32.EXE), which is a software extension that allows both the PolyCenter/AssetWORKS and Microsoft SMS environments for all Desktops products. This software extension enables PolyCenter/AssetWORKS and Microsoft SMS to read DMI information and report DMI data to applications.
- An applet with the ClientWORKS browser that allows users to update some information reported by the ClientWORKS application to both local and remote users. You can start this applet by double clicking the "Set ClientWORKS Information" icon. You can now enter your user name, phone number location, asset tag and chassis serial number. This information is stored for later retrieval either locally or remotely.
- REGISTRY.MIF, which allows the ClientWORKS browser to report information found in either the Windows 95 or Windows NT registry.

Before using ClientWORKS, be sure to read the ClientWORKS README.TXT in the ClientWORKS folder.

The following subsections discuss important information you should know about ClientWORKS.

Notes on the ClientWORKS Editor

In certain instances when accessing a remote node using the neighborhood version of the editor, you may find that selecting a node may take much longer than expected. This condition is normally due to processing taking place at the remote end. Eventually the remote node does respond.

When viewing a group that contains attributes that are listed as unsupported, the editor does not display the unsupported column. As a result, the attribute data aligns under the wrong heading. This problem does not exist in any of the supplied MIFs, but may occur if you install externally provided MIFs.

In certain situations, ill behaved instrumentation can hang the service layer causing the ClientWORKS browser to return an error. Thereafter, each time you access the service layer, the browser appears to browse forever. In this case, shutdown the browser and service layer manually by either rebooting (under Windows 95) or stopping and restarting the service layer (under Windows NT). Normal functionality is then restored. Make sure to note the group and attribute you were accessing when the error occurred and report it to the appropriate vendor.

Notes on Registry Instrumentation Initializer

If you select the Registry Instrumentation Initializer from the Digital grouping, the following message displays after the ClientWORKS Registry Instrumentation Initializer executes:

"Regci failure - The Registry MIF is not installed"

The message is not signifying a problem. You should read the ClientWORKS README.TXT in the ClientWORKS group. See the section on "Installing the Registry MIF."

Making ClientWORKS Data Visible through SNMP

ClientWORKS comes with SNMP subagents that make your computer visible to an SNMP console. Specifically, the ClientWORKS subagents provide HRMib support (RFC1514). Although these subagents are pre-installed, they are disabled in the factory installed software. Before you can enable them, you must first install TCP/IP, which is part of Windows 95.

To install TCP/IP, follow the Windows 95 help instructions for installing a network protocol. Once you have installed TCP/IP, you must install the Microsoft SNMP Master Agent as follows:

1. From Start, select Settings.
2. From Settings, select Control Panel.
3. From Control Panel, select Networks icon. The Network Property Sheets appears.
4. From the Configuration tab, click on Add. e Select Network Component Type dialog box appears.
5. Double-click on Service. The Select Network Service dialog box appears.
6. Click on Have Disk. The Install From Disk Dialog appears.
7. Type C:\WINDOWS\OPTIONS\CABS and press OK. The Open dialog box appears.
8. Select Snmp.inf and click OK. The Install from Disk screen is displayed.
9. Choose OK and follow the instructions displayed on your screen.

Your system is now visible through a remote SNMP.

PC Care (Windows 95 only)

When you run PC Care on Windows 95, you cannot minimize the tests. You can only minimize the current test.

Changing the Boot Sequence

Some legacy (non Plug and Play) devices, such as SCSI hard drive controllers with bootable ROM installed, are able to gain control over the boot process and initiate a boot sequence of their own. In this case, there is no consistent way for the BIOS to regain control if the device fails to boot.

Copyrights

Copyright Digital Equipment Corporation.
All Rights Reserved.

Microsoft and Windows 95 are registered trademarks of
Microsoft Corporation.

All other trademarks and registered trademarks are trademarks of their
respective holders.